

轻质柔软食品排吸管ATLAS

A5-003



应用:

- 轻质且非常柔韧的食品管，可用于食品物质如牛奶、饮料、果汁、酒类等的重力流、压力流和抽吸流的输送。推荐用于酿酒工业专用输送软管。

优点:

- 良好的柔性可满足小弯曲半径使用工况
- 白色光滑内胶符合FDA要求，防止细菌滋生
- 重量轻，方便安装及移动使用
- 适用温度范围广
- 不含塑化剂（邻苯二甲酸酯）

技术参数:

- 内胶：乙烯基丁腈橡胶，白色光滑（满足USDA和3-A标准要求）
- 增强层：合成纺织物螺旋缠绕并带有2根镀锌防锈螺旋钢丝
- 外胶：乙烯基丁腈橡胶，灰色（波纹状，包裹压印）
- 工作温度：-32°C 至+100°C

适用标准及认证:

- GB4806.11-2016
- GB31604.30-2016
- GB9685-2016
- FDA/USDA
- 3-A sanitary standard 18-03

Applications:

- A lightweight, highly flexible hose used for transferring food materials like milk, drinking, fruit juice, wine etc. in gravity flow, pressure or suction service.

Advantages:

- Extremely flexible to accept the smallest bending radius without kinking
- White and smooth tube does not propagate bacterial growth and complies with FDA requirements
- Lightweight for easily installation and movement
- Change in temperature have little effect due to the qualities of the rubber compound
- Phthalate free

Technical description:

- Tube: White NBR synthetic rubber
- Reinforcement: Synthetic textile fabric plies and two galvanized wire helix
- Cover: Gray NBR synthetic rubber, corrugated, wrapped impression
- Temperature Range: -32°C to +100°C

Standard/Approval:

- GB4806.11-2016
- GB31604.30-2016
- GB9685-2016
- FDA/USDA
- 3-A sanitary standard 18-03

轻质柔软食品排吸管

ATLAS

产品编码 No.	内径 in	mm	外径 mm	工作压力 bar	爆破压力 bar	耐负压 bar	弯曲半径 mm	重量 kg/m	包装长度 m
A5-003-0750	3/4"	19.1	29.4	10.3	40	0.9	45	0.62	60.96
A5-003-1000	1 "	25.4	35.7	10.3	40	0.9	50	0.79	60.96
A5-003-1250	1-1/4"	31.8	44.0	10.3	40	0.9	60	0.95	60.96
A5-003-1500	1-1/2"	38.1	48.8	10.3	40	0.9	64	1.15	60.96
A0-003-2000	2"	50.8	62.0	10.3	40	0.9	76	1.49	60.96
A0-003-2500	2-1/2"	63.5	76.2	10.3	40	0.9	127	2.17	60.96
A0-003-3000	3"	76.2	89.2	10.3	40	0.9	140	2.90	60.96
A0-003-4000	4"	101.6	115.6	10.3	40	0.9	191	3.85	60.96
A0-003-5000	5"	127.0	143.8	10.3	40	0.9	305	5.71	30.48
A0-003-6000	6"	152.4	169.2	10.3	40	0.9	432	6.77	30.48
A5-003-8000	8"	203.4	224.4	10.3	40	0.9	1016	12.75	30.48

