

# 硅胶蠕动泵管

## 9101

SUPPURE 9101-15

### 应用:

- 蠕动泵的流体输送
- 化学品的检验分析
- 药物生产输送和取样
- 食品饮料输送

### 优势:

- 灵活性高
- 铂金硫化工艺硅胶生产
- 高洁净室生产和包装
- 无气味, 不含重金属和有害物质
- 更好的透明度和使用寿命

### 技术参数:

- 材质: 铂金硫化硅胶
- 工作温度: -80°C至 +230°C
- 适用标准及标准: FDA CFR 177.2600、USP Class VI、RoSH

### Applications:

- Peristaltic pump based fluid transfer
- Chemical and analytical analysis
- Sanitary application
- Drug delivery and sampling
- Food and beverages transfer

### Advantage:

- Extremely flexible
- Manufactured by using platinum grade silicone rubber
- Manufactured and packaged in clean room of class 10000 facility
- Will not impart taste or odor
- Free of any heavy metals and hazardous substances
- Better transparency and higher shelf life compare to peroxide tubing

### Technical description:

- Tube: platinum grade silicone rubber
- Temperature: -80 C to +230 C
- Standard/Approval: FDA CFR 177.2600、USP Class VI、RoSH

## 硅胶蠕动泵管

## 9101

产品编码 No.	内径		外径		壁厚		包装长度 m
	in.	mm	in.	mm	in.	mm	
9101-13	1/32"	0.8	5/32"	4	1/16"	1.6	15/25
9101-14	1/16"	1.6	3/16"	4.8	1/16"	1.6	15/25
9101-15	3/16"	4.8	3/8"	9.6	3/32"	2.4	15/25
9101-16	1/8"	3.2	1/4"	6.4	1/16"	1.6	15/25
9101-17	1/4"	6.4	3/8"	9.6	1/16"	1.6	15/25
9101-18	5/16"	7.9	7/16"	11.1	1/16"	1.6	15/25
9101-19	3/32"	2.4	7/32"	5.6	1/16"	1.6	15/25
9101-24	1/4"	6.4	7/16"	11.2	3/32"	2.4	15/25
9101-25	3/16"	4.8	5/16"	8	1/16"	1.6	15/25
9101-26	1/4"	6.4	1/2"	12.7	1/8"	3.2	15/25
9101-35	5/16"	7.9	1/2"	12.7	3/32"	2.4	15/25
9101-36	3/8"	9.6	9/16"	14.4	3/32"	2.4	15/25
9101-70	3/8"	9.6	3/4"	19.1	3/16"	4.8	15/25
9101-73	3/8"	9.6	5/8"	16	1/8"	3.2	15/25
9101-82	1/2"	12.7	3/4"	19.1	1/8"	3.2	15/25
9101-86	3/8"	9.6	7/8"	22.4	1/4"	6.4	15/25
9101-87	1/2"	12.7	1"	25.4	1/4"	6.4	15/25
9101-88	1/2"	12.7	7/8"	22.4	3/16"	4.8	15/25
9101-89	5/8"	15.9	1"	25.4	3/16"	4.8	15/25
9101-91	3/4"	19.1	1-1/4"	31.8	1/4"	6.4	15/25
9101-92	1"	25.4	1-3/8"	35	3/16"	4.8	15/25

